

WS3

WATER SPECIALIST 3" CONTROL VALVE



Optional 3" Meter

- 3" top mount or side mount control valve suited for commercial and industrial applications
- Lead free brass valve body
- Economical stainless steel optional meter assembly
- Service flow rate 250 gpm (946 lpm), Backwash flow rate 220 gpm (833 lpm)
- Solid state microprocessor with easy access front removable POD
- Front panel display for Time of Day, Current Flow Rate, Totalizer and Volume/Days until Regeneration
- Four methods to initiate the down flow regeneration; meter delayed, meter immediate, time clock delayed, or pressure differential
- Fully programmable regeneration cycle sequences (maximum 9)
- Fully programmable regeneration cycle times
- Treated water regenerant refill
- Days override feature; 1-28 days available
- Capacitor back-up with up to 24 hour power carry over
- 24-volt output AC adapter provides safe and easy installation
- Reliable and proven DC drive

Water Specialist 3" Control Specifications

Inlet/Outlet (1)	3" Female NPT or BSPT
Cycles	up to 9
Valve Material	Lead free brass
Regeneration	Downflow

CONTROL VALVE FLOW RATES

Service @ 15 psi/1 bar drop.....	250 gpm (946 lpm)
Backwash @ 25 psi/1.7 bar drop.....	220 gpm (833 lpm)
Cv Service.....	64.6
Cv Backwash.....	44.0

OPERATING PRESSURES

Minimum/Maximum	20 - 125 psi (1.4 - 8.6 bar)
-----------------------	------------------------------

OPERATING TEMPERATURES

Minimum/Maximum	40° - 110° F (4° - 43° C)
-----------------------	---------------------------

METER SPECIFICATIONS

Accuracy.....	± 5%
Flow Rate Range	3.5 - 350 gpm (13.3 - 1325 lpm)
Volume Range	10 - 999,000 gallons (38 - 3,796.2 liters x1000)
Totalizer	1,000 - 999,999,000 gallons (3,786 - 3,785,407.9 liters x1000)

DIMENSIONS & WEIGHT

Distributor Pilot	
Valve Bodies with 3" Female NPT Inlet & Outlet.....	3.5" OD (3" NPS)
Valve Bodies with 3" Female BSPT Inlet & Outlet	90mm OD
Drain Line Connection	3" Female NPT "No Groove Lock"
Brine Line Adapters Included.....	1" Male NPT elbow and ¾" x 1" solvent weld elbow
Mounting Base.....	6" Flange or Side Mount
Height From Top Of Tank.....	12.25" (311mm)
Shipping Weight Without Optional Meter	57 lbs (25.9 Kg)

ELECTRICAL SPECIFICATIONS

	AC Adapter	
	U.S.	International
Supply Voltage	120V AC.....	230V AC
Supply Frequency.....	60 Hz.....	50Hz
Output Voltage	24V AC.....	24V AC
Output Current	750 mA.....	750mA

TANK APPLICATIONS

Water Softener	18" - 63" Diameter with standard injectors, to 96" with Brine Pump
Water Filter (2)	18" - 63" Diameter

CYCLES OF OPERATION

Choose up to nine regeneration cycles, in any order, with a wide range of available values:

Cycle	Range of values
Backwash.....	1 - 95 minutes
Brine (draw)	1 - 180 minutes
Slow Rinse	1 - 95 minutes
Fast Rinse	1 - 95 minutes
Refill	0.1 - 99 minutes
Hold (service)	1 - 480 minutes

Options: Backwash Filter

Compatible with the following typical concentrations of regenerants or chemicals: Sodium chloride, potassium chloride, potassium permanganate, sodium bisulfite, chlorine and chloramines